

Klett-Kabelbinder

Produkt

- Klett-Kabelbinder

Einsatzbereich

- Maschinenbau
- Anlagenbau
- Apparatebau
- Kabelkonfektion

Eigenschaften

- einfache und schnelle Montage
- einfaches Öffnen und Schliessen
- ohne Metallteile
- frei von Lackbenetzung störende Substanzen (LABSfrei), RoHS-konform

Technische Daten

Material	Polyethylene
Temperaturbereich	-35 °C bis +70 °C
Brennverhalten	Flammwidrig
Zertifizierung	CE

Farbe: schwarz

Fragen Sie uns für andere Farben an

velcro cable ties

product

- velcro cable ties

area of application

- mechanical engineering
- plant engineering and construction
- construction of apparatus
- cable assemblies

properties

- easy to mount
- can be opened and closed thousands of times
- no metal parts
- free from paint wetting Interfering substances (LABS-free), RoHS Compliant

technical data

material	Polyethylene
temperature range	-35 °C up to +70 °C
flammability	flame retardant
approvals	CE

colour: black

contact us for other colours



Art.nr part-no	Dimension mm	Bündel Ø max. bundle Ø max.	VPE packing unit	Preis CHF. /100 Stk. price CHF. / 100 pcs.
black				
251382	150x12	35	20	36.20
251326	200x12	40	20	44.40
251364	300x12	70	100	91.40
251366	300x16	70	100	96.20

Klett-Kabelbinder mit Montageclip

Produkt

- Klett-Kabelbinder

Einsatzbereich

- Maschinenbau
- Anlagenbau
- Apparatebau
- Service und Unterhalt

Eigenschaften

- einfache und schnelle Montage
- einfaches Öffnen und Schliessen
- ohne Metallteile
- frei von Lackbenetzung störende Substanzen (LABSfrei), RoHS-konform

Technische Daten

Material	Polyethylene / Polyamid
Temperaturbereich	-35 °C bis +70 °C
Brennverhalten	Flammwidrig
Zertifizierung	CE

Farbe: schwarz

velcro cable ties with mounting clip

product

- velcro cable ties

area of application

- mechanical engineering
- plant engineering and construction
- construction of apparatus
- service and maintenance

properties

- easy to mount
- can be opened and closed thousands of times
- no metal parts
- free from paint wetting Interfering substances (LABS-free), RoHS Compliant

technical data

material	Polyethylene / Polyamid
temperature range	-35 °C up to +70 °C
flammability	flame retardant
approvals	CE

colour: black



Art.nr part-no	Breite Clip mm width clip mm	Bündel Ø bundle Ø	Schraube screw	VPE packing unit	Preis CHF. /1 Stk. price CHF. / 1 pcs.
black					
251751	15	6-20	4.6	20	3.60
251752	25	6-35	4.6	35	3.80
251753	35	6-60	4.6	100	4.20